Gang Channel Self-locking Nut Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-440-9906

| Thread Class: |
|------------------------------------|
| 3b |
| Thread Direction: |
| Right-hand |
| Locking Feature: |
| Prevailing torque all metal design |
| Counterbore Diameter: |
| 0.194 inches nut |
| Lubrication: |
| Dry film lubricant |
| Overall Length: |
| 2.186 inches |
| Overall Width: |
| 0.416 inches |
| Nut Style: |
| Gang channel, self locking |
| Channel Style: |
| Straight type |
| Assemblyheight: |
| 0.250 inches |
| Channel Height: |
| 0.250 inches |
| Nut Spacing: |
| 0.750 inches |
| Nut Counterbore Depth: |
| 0.027 inches nut |
| Tempurature Rating: |
| 450.0 degrees fahrenheit |
| Nut Quantity: |
| 3 |
| Thread Series: |
| Unjf |
| Features Provided: |
| Floating nut |
| Thready Qty Per Inch (tpi): |
| 32 |
| Hardness Rating: |
| 49.0 rockwell c |
| Thread Size: |
| 0.190 inches |
| Material: |
| |
| Steel nut |

Gang Channel Self-locking Nut Assembly - Page 2 of 2



Surface Treatment:

Passivate channel

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification 1st treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0