

View Online at <https://aerobasegroup.com/nsn/5310-00-486-4677>

Hole Diameter:

Between 0.260 inches and 0.270 inches

Outside Diameter:

Between 0.454 inches and 0.464 inches

Recess Diameter:

Between 0.332 inches and 0.342 inches

Material Thickness:

Between 0.075 inches and 0.095 inches

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

Between 40.0 rockwell c and 46.0 rockwell c

Recess Angle:

Between 88.0 degrees and 92.0 degrees

Surface Finish:

32.0 microinches top

Special Features:

0.290 in. Min, 0.310 in. Maximum spherical radius one side of bearing surface

Material Specification:

Mil-s-6758 military specification 1st material response or mil-s-18729 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6358 assn standard 2nd material response or astm a193 assn standard 3rd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Style Designator:

Recessed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A022b0

Mil-std (military Standard):

Mil-s-6758 spec.