NSN 5310-00-499-7706

Plate Nut Spacer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-00-499-7706

| Mounting Hole Diameter: |
|---|
| Between 0.102 inches and 0.108 inches |
| Nut Style: |
| Plate nut spacer |
| Nut Length: |
| 1.281 inches |
| Thru-hole Diameter: |
| Between 0.322 inches and 0.332 inches |
| Plate Thickness: |
| 0.032 inches |
| Plate Width: |
| 0.500 inches |
| Nut Mounting Provision: |
| Straight holes |
| Mounting Hole Arrangement Style: |
| 2 holes |
| Distance From Aperture Center To Mounting Hole Center: |
| Between 0.497 inches and 0.503 inches |
| Center To Center Distance Between Mounting Holes Along Length: |
| Between 0.998 inches and 1.002 inches |
| Material: |
| Steel comp 1010 or steel comp 1020 or steel comp 1025 or steel comp 4130 |
| Material Specification: |
| Asis or sae assn standard 1st material response or mil-s-7952 military specification 2nd material response or mil-s-7952 military |
| specification 3rd material response or mil-s-18729 cond n military specification 4th material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 2 federal specification single treatment response |
| Specification Data: |
| 80205-nas463 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A021a0 |
| Mil-std (military Standard): |
| Mil-s-7952 spec. |