## NSN 5310-00-500-3523

Assembled Washer Self-locking Nut - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5310-00-500-3523 |
|---|
| Thread Class:   |
| 3b  |
| Thread Direction:   |
| Right-hand  |
| Locking Feature:  |
| Prevailing torque all metal design                            |
| Washer Outside Diameter:                                      |
| 1.185 inches  |
| Counterbore Diameter:   |
| 0.785 inches nut  |
| Overall Height:   |
| 0.900 inches  |
| Nut Style:  |
| Flat with turned up edge                                      |
| Nut Counterbore Depth:  |
| 0.050 inches nut  |
| Width Across Flats:   |
| Between 0.928 inches and 0.940 inches                         |
| Tempurature Rating:   |
| Between 450.0 degrees fahrenheit and 900.0 degrees fahrenheit |
| Thread Series:  |
| Unjf  |
| Thready Qty Per Inch (tpi):                                   |
| 16  |
| Thread Size:  |
| 0.750 inches  |
| Material:   |
| Iron alloy 660  |
| Surface Treatment:  |
| Silver threads  |
| Surface Treatment Specification:                              |
| Ams 2410 assn standard single treatment response threads      |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A021a0  |