NSN 5310-00-515-9960

Lock Washer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-00-515-9960

Hole Diameter: Between 0.382 inches and 0.393 inches Outside Diameter: 0.673 inches Material Thickness: Between 0.070 inches and 0.080 inches Hardness Rating: Between 45.0 rockwell c and 53.0 rockwell c Heat Treatment: Quenched and tempered Style Designator: Split helical-right hand Test Data Document: 81348-ffw84 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environr and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: A class and 1 style Shelf Life: N/a	
Outside Diameter: 0.673 inches Material Thickness: Between 0.070 inches and 0.080 inches Hardness Rating: Between 45.0 rockwell c and 53.0 rockwell c Heat Treatment: Quenched and tempered Style Designator: Split helical-right hand Test Data Document: 81348-ffw84 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: A class and 1 style Shelf Life:	
Material Thickness: Between 0.070 inches and 0.080 inches Hardness Rating: Between 45.0 rockwell c and 53.0 rockwell c Heat Treatment: Quenched and tempered Style Designator: Split helical-right hand Test Data Document: 81348-ffw84 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: A class and 1 style Shelf Life:	
Material Thickness: Between 0.070 inches and 0.080 inches Hardness Rating: Between 45.0 rockwell c and 53.0 rockwell c Heat Treatment: Quenched and tempered Style Designator: Split helical-right hand Test Data Document: 81348-ffw84 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: A class and 1 style Shelf Life:	
Between 0.070 inches and 0.080 inches Hardness Rating: Between 45.0 rockwell c and 53.0 rockwell c Heat Treatment: Quenched and tempered Style Designator: Split helical-right hand Test Data Document: 81348-ffw84 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: A class and 1 style Shelf Life:	
Hardness Rating: Between 45.0 rockwell c and 53.0 rockwell c Heat Treatment: Quenched and tempered Style Designator: Split helical-right hand Test Data Document: 81348-ffw84 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: A class and 1 style Shelf Life:	
Between 45.0 rockwell c and 53.0 rockwell c Heat Treatment: Quenched and tempered Style Designator: Split helical-right hand Test Data Document: 81348-ffw84 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: A class and 1 style Shelf Life:	
Heat Treatment: Quenched and tempered Style Designator: Split helical-right hand Test Data Document: 81348-ffw84 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: A class and 1 style Shelf Life:	
Quenched and tempered Style Designator: Split helical-right hand Test Data Document: 81348-ffw84 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: A class and 1 style Shelf Life:	
Style Designator: Split helical-right hand Test Data Document: 81348-ffw84 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: A class and 1 style Shelf Life:	
Split helical-right hand Test Data Document: 81348-ffw84 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: A class and 1 style Shelf Life:	
Test Data Document: 81348-ffw84 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: A class and 1 style Shelf Life:	
81348-ffw84 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: A class and 1 style Shelf Life:	
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: A class and 1 style Shelf Life:	
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: A class and 1 style Shelf Life:	rmat
Specification Or Standard: A class and 1 style Shelf Life:	enta
A class and 1 style Shelf Life:	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A022b0	