NSN 5310-00-526-9081

Plate Nut Spacer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-00-526-9081

| Mounting Hole Diameter: |
|--|
| 0.105 inches |
| Nut Style: |
| Plate nut spacer |
| Nut Length: |
| 1.250 inches |
| Thru-hole Diameter: |
| 0.322 inches |
| Plate Thickness: |
| 0.063 inches |
| Plate Width: |
| 0.500 inches |
| Nut Mounting Provision: |
| Straight holes |
| Mounting Hole Arrangement Style: |
| 2 holes |
| Distance From Aperture Center To Mounting Hole Center: |
| 0.500 inches |
| Center To Center Distance Between Mounting Holes Along Length: |
| 0.312 inches |
| |
| Material: |
| Material: Aluminum alloy 5052 |
| |
| Aluminum alloy 5052 |
| Aluminum alloy 5052 Material Specification: |
| Aluminum alloy 5052 Material Specification: Qq-a-250/8 federal specification single material response |
| Aluminum alloy 5052 Material Specification: Qq-a-250/8 federal specification single material response Surface Treatment: |
| Aluminum alloy 5052 Material Specification: Qq-a-250/8 federal specification single material response Surface Treatment: Anodize |
| Aluminum alloy 5052 Material Specification: Qq-a-250/8 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: |
| Aluminum alloy 5052 Material Specification: Qq-a-250/8 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response |
| Aluminum alloy 5052 Material Specification: Qq-a-250/8 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: |
| Aluminum alloy 5052 Material Specification: Qq-a-250/8 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard |
| Aluminum alloy 5052 Material Specification: Qq-a-250/8 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: |
| Aluminum alloy 5052 Material Specification: Qq-a-250/8 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a |
| Aluminum alloy 5052 Material Specification: Qq-a-250/8 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a |
| Aluminum alloy 5052 Material Specification: Qq-a-250/8 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: |
| Aluminum alloy 5052 Material Specification: Qq-a-250/8 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: |
| Aluminum alloy 5052 Material Specification: Qq-a-250/8 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No |
| Aluminum alloy 5052 Material Specification: Qq-a-250/8 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: |