## NSN 5310-00-526-9081

Plate Nut Spacer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-00-526-9081

| Mounting Hole Diameter:  |
|--|
| 0.105 inches   |
| Nut Style:   |
| Plate nut spacer   |
| Nut Length:  |
| 1.250 inches   |
| Thru-hole Diameter:  |
| 0.322 inches   |
| Plate Thickness:   |
| 0.063 inches   |
| Plate Width:   |
| 0.500 inches   |
| Nut Mounting Provision:  |
| Straight holes   |
| Mounting Hole Arrangement Style:   |
| 2 holes  |
| Distance From Aperture Center To Mounting Hole Center:   |
| 0.500 inches   |
| Center To Center Distance Between Mounting Holes Along Length:   |
| 0.312 inches   |
|  |
| Material:  |
| Material: Aluminum alloy 5052  |
|  |
| Aluminum alloy 5052  |
| Aluminum alloy 5052  Material Specification:   |
| Aluminum alloy 5052  Material Specification:  Qq-a-250/8 federal specification single material response  |
| Aluminum alloy 5052  Material Specification:  Qq-a-250/8 federal specification single material response  Surface Treatment:  |
| Aluminum alloy 5052  Material Specification:  Qq-a-250/8 federal specification single material response  Surface Treatment:  Anodize   |
| Aluminum alloy 5052  Material Specification:  Qq-a-250/8 federal specification single material response  Surface Treatment:  Anodize  Surface Treatment Specification:   |
| Aluminum alloy 5052  Material Specification:  Qq-a-250/8 federal specification single material response  Surface Treatment:  Anodize  Surface Treatment Specification:  Mil-a-8625, type 2 military specification single treatment response  |
| Aluminum alloy 5052  Material Specification: Qq-a-250/8 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data:   |
| Aluminum alloy 5052  Material Specification: Qq-a-250/8 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard   |
| Aluminum alloy 5052  Material Specification:  Qq-a-250/8 federal specification single material response  Surface Treatment:  Anodize  Surface Treatment Specification:  Mil-a-8625, type 2 military specification single treatment response  Specification Data:  80205-nas463 professional/industrial association standard  Shelf Life:   |
| Aluminum alloy 5052  Material Specification: Qq-a-250/8 federal specification single material response  Surface Treatment: Anodize  Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response  Specification Data: 80205-nas463 professional/industrial association standard  Shelf Life: N/a   |
| Aluminum alloy 5052  Material Specification: Qq-a-250/8 federal specification single material response  Surface Treatment: Anodize  Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response  Specification Data: 80205-nas463 professional/industrial association standard  Shelf Life: N/a   |
| Aluminum alloy 5052  Material Specification: Qq-a-250/8 federal specification single material response  Surface Treatment: Anodize  Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response  Specification Data: 80205-nas463 professional/industrial association standard  Shelf Life: N/a  Unit Of Measure:                       |
| Aluminum alloy 5052  Material Specification: Qq-a-250/8 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization:          |
| Aluminum alloy 5052  Material Specification: Qq-a-250/8 federal specification single material response  Surface Treatment: Anodize  Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response  Specification Data: 80205-nas463 professional/industrial association standard  Shelf Life: N/a  Unit Of Measure: Demilitarization: No  |
| Aluminum alloy 5052  Material Specification: Qq-a-250/8 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: |