NSN 5310-00-550-2123

Plate Nut Spacer - Page 1 of 2



| view Online at https://aerobasegroup.com/nsn/5510-00-550-2125 |
|--|
| Mounting Hole Diameter: |
| Between 0.102 inches and 0.108 inches |
| Nut Style: |
| Plate nut spacer |
| Nut Length: |
| Between 1.266 inches and 1.296 inches |
| Thru-hole Diameter: |
| Between 0.322 inches and 0.332 inches |
| Plate Thickness: |
| Between 0.059 inches and 0.067 inches |
| Plate Width: |
| Between 0.485 inches and 0.515 inches |
| Nut Mounting Provision: |
| Countersunk holes |
| Mounting Provision Location: |
| Nut projection side |
| Mounting Hole Arrangement Style: |
| 2 holes |
| Distance From Aperture Center To Mounting Hole Center: |
| Between 0.497 inches and 0.503 inches |
| Center To Center Distance Between Mounting Holes Along Length: |
| Between 0.998 inches and 1.002 inches |
| Mounting Hole Countersink Angle: |
| 100.0 degrees |
| Material: |
| Aluminum alloy 5052 |
| Material Specification: |
| Qq-a-250/8, alloy 5052, h32 federal specification 1st material response or qq-a-250/8, h34 federal specification 2nd material response o |
| qq-b-250/8, h36 federal specification 3rd material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625, type 2 military specification single treatment response |
| Specification Data: |
| 80205-nas463 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No. |

Fiig: A021a0

NSN 5310-00-550-2123

Plate Nut Spacer - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.