NSN 5310-00-556-6821

Double Hexagon Extended Washer Self-locking Nut - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5310-00-556-6821 |
|--|
| Thread Class: |
| 3b |
| Thread Direction: |
| Right-hand |
| Locking Feature: |
| Prevailing torque all metal design |
| Washer Outside Diameter: |
| 0.380 inches |
| Counterbore Diameter: |
| 0.211 inches nut and 0.221 inches nut |
| Lubrication: |
| Dry film lubricant |
| Overall Height: |
| Between 0.223 inches and 0.243 inches |
| Nut Style: |
| Double hexagon |
| Washer Thickness: |
| Between 0.072 inches and 0.087 inches |
| Nut Counterbore Depth: |
| 0.072 inches nut and 0.087 inches nut |
| Width Across Flats: |
| Between 0.213 inches and 0.221 inches |
| Tempurature Rating: |
| 450.0 degrees fahrenheit |
| Thread Series: |
| Unjf |
| Thready Qty Per Inch (tpi): |
| 32 |
| Hardness Rating: |
| Between 35.0 rockwell c and 40.0 rockwell c |
| Thread Size: |
| 0.190 inches |
| Material: |
| Steel comp 8740 washer |
| Material Specification: |
| Ams6322 assn standard single material response washer or mil-s-6049 comp 8740 military specification single material response washer |
| Surface Treatment: |
| Cadmium nut |
| Surface Treatment Specification: |
| Qq-p-416 type2, class3 federal specification single treatment response washer |

N/a

Shelf Life:

NSN 5310-00-556-6821

Double Hexagon Extended Washer Self-locking Nut - Page 2 of 2



| Demilitarization: |
|------------------------------|
| No |
| Fiig: |
| A021a0 |
| Mil-std (military Standard): |

Mil-s-6049 spec.

Unit Of Measure: