

View Online at https://aerobasegroup.com/nsn/5310-00-558-0952

| Thread Class:                           |
|---|
| 3b                                      |
| Thread Direction:                       |
| Right-hand                              |
| Locking Feature:                        |
| Prevailing torque all metal design      |
| Counterbore Diameter:                   |
| 0.202 inches nut                        |
| Lubrication:                            |
| Dry film lubricant                      |
| Overall Length:                         |
| 72.000 inches                           |
| Overall Width:                          |
| 0.452 inches                            |
| Nut Style:                              |
| Gang channel, self locking              |
| Removable Nut Manufacturer Code:        |
| 76301                                   |
| Channel Style:                          |
| Straight type                           |
| Assemblyheight:                         |
| 0.309 inches                            |
| Channel Height:                         |
| 0.250 inches                            |
| Nut Spacing:                            |
| 1.000 inches                            |
| Nut Counterbore Depth:                  |
| 0.125 inches nut                        |
| Removable Nut Manufacturer Part Number: |
| St3m445a3m2                             |
| Tempurature Rating:                     |
| 350.0 degrees fahrenheit                |
| Nut Quantity:                           |
| 72                                      |
| Thread Series:                          |
| Unjf                                    |
| Features Provided:                      |
| Floating nut                            |
| Thready Qty Per Inch (tpi):             |
| 32                                      |
| Thread Size:                            |
| 0.190 inches                            |
|   |



#### **Special Features:**

Furnished with a steel spring clip

# Material:

Steel nut

# Material Specification:

Qq-a-250/13, temper t6 federal specification single material response channel

### Surface Treatment:

Cadmium nut

# Surface Treatment Specification:

Qq-p-416 federal specification single treatment response nut

## **Specification Data:**

76301-st3-543 manufacturers standard

Shelf Life:

N/a

### Unit Of Measure:

--

## Demilitarization:

No

# Fiig:

A021a0

### Mil-std (military Standard):

Mil-a-8625 spec.