

View Online at https://aerobasegroup.com/nsn/5310-00-558-0958

| Thread Class: |
|---|
| 3b |
| Thread Direction: |
| Right-hand |
| Locking Feature: |
| Prevailing torque all metal design |
| Counterbore Diameter: |
| 0.202 inches nut |
| Lubrication: |
| Dry film lubricant |
| Overall Length: |
| 72.000 inches |
| Overall Width: |
| 0.452 inches |
| Nut Style: |
| Gang channel, self locking |
| Removable Nut Manufacturer Code: |
| 76301 |
| Channel Style: |
| Straight type |
| Assemblyheight: |
| 0.231 inches |
| Channel Height: |
| 0.250 inches |
| Nut Spacing: |
| 1.000 inches |
| Nut Counterbore Depth: |
| 0.070 inches nut |
| Removable Nut Manufacturer Part Number: |
| St3m445a3m1 |
| Tempurature Rating: |
| 350.0 degrees fahrenheit |
| Nut Quantity: |
| 72 |
| Thread Series: |
| Unjf |
| Features Provided: |
| Floating nut |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.190 inches |
| |



Special Features:

Furnished with a steel spring clip

Material:

Steel nut

Material Specification:

Qq-a-250/13, temper t6 federal specification single material response channel

Surface Treatment:

Cadmium nut

Surface Treatment Specification:

Qq-p-416 federal specification single treatment response nut

Specification Data:

76301-st3-543 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-a-8625 spec.