

View Online at <https://aerobasegroup.com/nsn/5310-00-558-7146>

Mounting Hole Diameter:

Between 0.102 inches and 0.108 inches

Nut Style:

Plate nut spacer

Nut Length:

Between 0.954 inches and 0.984 inches

Thru-hole Diameter:

Between 0.260 inches and 0.270 inches

Plate Thickness:

Between 0.059 inches and 0.067 inches

Plate Width:

Between 0.391 inches and 0.421 inches

Nut Mounting Provision:

Countersunk holes

Mounting Provision Location:

Nut projection side

Mounting Hole Arrangement Style:

2 holes

Distance From Aperture Center To Mounting Hole Center:

Between 0.341 inches and 0.347 inches

Center To Center Distance Between Mounting Holes Along Length:

Between 0.686 inches and 0.690 inches

Mounting Hole Countersink Angle:

100.0 degrees

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8, alloy 5052, temper h32 federal specification 1st material response or qq-a-250/8, h34 federal specification 2nd material response or qq-a-250/8, a36 federal specification 3rd material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Specification Data:

80205-nas463 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-a-8625 spec.