

View Online at https://aerobasegroup.com/nsn/5310-00-565-3933

| Thread Class: |
|--|
| 3b |
| Thread Direction: |
| Right-hand |
| Locking Feature: |
| Prevailing torque all metal design |
| Washer Outside Diameter: |
| 1.160 inches |
| Counterbore Diameter: |
| 0.910 inches nut and 0.925 inches nut |
| Overall Height: |
| Between 0.330 inches and 0.375 inches |
| Nut Style: |
| Double hexagon |
| Nut Counterbore Depth: |
| 0.040 inches nut and 0.065 inches nut |
| Width Across Flats: |
| Between 0.927 inches and 0.944 inches |
| Thread Series: |
| Unjef |
| Thready Qty Per Inch (tpi): |
| 20 |
| Hardness Rating: |
| Between 34.0 rockwell c and 41.0 rockwell c |
| Thread Size: |
| 0.875 inches |
| Material: |
| Steel comp 8740 |
| Material Specification: |
| Ams 6322 assn standard single material response |
| Precious Material: |
| Silver |
| Surface Treatment: |
| |
| Silver |
| Surface Treatment Specification: |
| Ams 2410 assn standard single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |



Fiig: A021a0