NSN 5310-00-565-7042

Sleeve Nut - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-00-565-7042

| Thread Class: | |
|------------------|---|
| 2b | |
| Thread Direction | on: |
| Right-hand | |
| Flange Diamete | er: |
| Between 0.431 | inches and 0.433 inches |
| Flange Thickne | ess: |
| Between 0.281 | inches and 0.311 inches |
| Nut Style: | |
| Sleeve | |
| Nut Diameter: | |
| Between 0.308 | inches and 0.310 inches |
| Nut Length: | |
| 0.156 inches | |
| Cross-sectiona | al Shape: |
| Round nut | |
| Thread Series: | |
| Unf | |
| Thready Qty Po | er Inch (tpi): |
| 28 | |
| Hardness Ratii | ng: |
| Between 34.0 rd | ockwell c and 38.0 rockwell c |
| Thread Size: | |
| 0.250 inches | |
| Material: | |
| Steel | |
| Surface Treatm | nent: |
| Nickel | |
| Surface Treatm | nent Specification: |
| Mil-c-26074, cla | iss 1 military specification single treatment response or qq-n-290, class 1, grade c federal specification single treatment |
| response | |
| Shelf Life: | |
| N/a | |
| Unit Of Measur | re: |
| | |
| Demilitarizatio | n: |
| No | |
| Fiig: | |
| A021a0 | |
| Mil-std (militar | y Standard): |
| Mil-c-26074 spe | ЭС. |