

View Online at <https://aerobasegroup.com/nsn/5310-00-584-5272>

**Hole Diameter:**

Between 0.509 inches and 0.523 inches

**Outside Diameter:**

0.873 inches

**Material Thickness:**

Between 0.125 inches and 0.135 inches

**End Application:**

Elevators, aircraft, fire pumps, boilers, 1200 psi, I.P. Compressors, airborne mobile dir air spt ctl (2id), (02m jul83)(an/uyq-3a)vehicle, aircraft refueler r-14, tactical data system, an/uya- (v), sentinel radar system, support equipment, b-1 aircraft, communications terminal, satellitean/gsc-39(v)1; 2320-01-097-0248, 2320-01-097-0249, 2320-01-100-7672, 2320-01-097-0260, 2320-01-195-7641, hemtt family (heavy expanded mobility tactical trucks); 2320-01-097-0260 hiab crane (hemtt); 3990-01-442-1939 bap (bridge adapter pallet) ; mrap rg-31; mrap rg-33 and rg-33 auv; mrap buffalo mk2a2

**Hardness Rating:**

Between 45.0 rockwell c and 53.0 rockwell c

**Criticality Code Justification:**

Feat

**Special Features:**

Weapon system essential

**Material:**

Steel comp 1060 or steel comp 1561 or steel comp 1064 or steel comp 1065 or steel comp 1566 or steel comp 1069 or steel comp 1070 or steel comp 1572 or steel comp 1075 or steel comp 1078 or steel comp 1080

**Material Specification:**

66 federal standard all material responses

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Style Designator:**

Split helical-right hand

**Specification Or Standard:**

2 style and a class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A022b0