

View Online at <https://aerobasegroup.com/nsn/5310-00-596-7691>

Hole Diameter:

Between 0.195 inches and 0.204 inches

Outside Diameter:

Between 0.395 inches and 0.410 inches

Material Thickness:

Between 0.020 inches and 0.025 inches

End Application:

W/s: shipboard material handling equipment (mhe); airborne mobile dir air spt ctl (2id), (02m jul83)(an/uyq-3a); aircraft (ac-130h, mc-130h, ec-130e, hc-130); close in weapon system (ciws-phalanx); support equipment, b-1 aircraft; missile, air intercept, sidewinder (aim-9); fire control system, missile mk 74 (fcs); engine, aircraft tf33-p-3/5/9 (c/ec-135, b-52h); gun mount, mk 75 (gm); fire pumps

Hardness Rating:

Between 40.0 rockwell c and 50.0 rockwell c

Material:

Steel comp 1050 or steel comp 1551 or steel comp 1059 or steel comp 1060 or steel comp 1561 or steel comp 1064

Material Specification:

66 federal standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Style Designator:

Flat external teeth

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A022b0