## NSN 5310-00-596-7693

Lock Washer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-00-596-7693

**Hole Diameter:** 

Between 0.168 inches and 0.176 inches

**Outside Diameter:** 

Between 0.365 inches and 0.381 inches

**Material Thickness:** 

Between 0.018 inches and 0.023 inches

**End Application:** 

Vehicle, aircraft refueler r-14, test consoles, mini-sace, test set, ttu-205, airborne mobile dir air spt ctl (2id), (02m jul83)(an/uyq-3a), missile, air-to-air, phoenix (aim-54), fire pumps, I.P. Compressors, support equipment, b-1 aircraft, lav, anti-tank, air compressors, high pressure; 2320-01-304-2277 pls (palletized loading system)

## Hardness Rating:

Between 40.0 rockwell c and 50.0 rockwell c

Material:

Steel comp 1050 or steel comp 1551 or steel comp 1059 or steel comp 1060 or steel comp 1561 or steel comp 1064

**Material Specification:** 

66 federal standard all material responses

**Surface Treatment:** 

Cadmium and chromate

**Surface Treatment Specification:** 

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Style Designator:** 

Flat external teeth

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A022b0