
Plate Self-locking Nut - Page 1 of 2





## **Thread Class:** 3b **Thread Direction: Right-hand** Locking Feature: Prevailing torque all metal design **Overall Height:** Between 0.201 inches and 0.231 inches Mounting Hole Diameter: 0.066 mils and 0.071 centimeters Nut Style: Plate Nut Length: 0.545 inches Nut Height: 0.075 inches **Plate Thickness:** 0.045 inches Plate Width: Between 0.290 inches and 0.357 inches **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.167 inches and 0.177 inches Center To Center Distance Between Mounting Holes Along Length: Between 0.341 inches and 0.345 inches **Tempurature Rating:** 900.0 degrees fahrenheit **Thread Series:** Unjc **Features Provided:** Floating nut Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.112 inches Material: Steel comp 321 cap or iron alloy 660 cap **Material Specification:**

Bams 5510 assn standard 1st material response cap or ams 5525 assn standard 2nd material response cap or ams 5732 assn standard 3rd

material response cap or ams 5737 assn standard 4th material response cap

## Precious Material And Location:

Nut silver

## NSN 5310-00-601-9741

Plate Self-locking Nut - Page 2 of 2



**Precious Material:** 

Silver

Surface Treatment:

Passivate shell or silver shell

Surface Treatment Specification:

Ams 2410 assn standard single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0