NSN 5310-00-608-2426

Plate Self-locking Nut - Page 1 of 2





Thread Class: 3b **Thread Direction: Right-hand** Locking Feature: Prevailing torque all metal design Mounting Hole Diameter: 0.098 mils and 0.103 centimeters Nut Style: Plate Nut Length: Between 0.920 inches and 0.950 inches Nut Height: Between 0.207 inches and 0.227 inches **Plate Thickness:** Between 0.050 inches and 0.070 inches Plate Width: 0.328 inches **Nut Mounting Provision:** Countersunk holes **Mounting Provision Location:** Opposite nut projection side Mounting Hole Arrangement Style: 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.329 inches and 0.359 inches Center To Center Distance Between Mounting Holes Along Length: Between 0.310 inches and 0.314 inches **Tempurature Rating:** 250.0 degrees fahrenheit **Thread Series:** Unc Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches **Mounting Hole Countersink Angle:** Between 98.0 degrees and 102.0 degrees Material: Aluminum alloy 2024 Surface Treatment: Anodize

NSN 5310-00-608-2426

Plate Self-locking Nut - Page 2 of 2



Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-a-8625 spec.