AeroBase Group

View Online at https://aerobasegroup.com/nsn/5310-00-611-4414

Thread Class:
3b
Thread Direction:
Right-hand
Lubrication:
Dry film lubricant
Overall Length:
71.190 inches
Overall Width:
0.416 inches
Nut Style:
Gang channel, self locking
Channel Style:
Straight type
Assemblyheight:
0.250 inches
Nut Spacing:
Between 1.240 inches and 1.260 inches
Tempurature Rating:
300.0 degrees fahrenheit
Nut Quantity:
57
Thread Series:
Unf
Features Provided:
Floating nut
•
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 32
Thready Qty Per Inch (tpi): 32 Thread Size:
Thready Qty Per Inch (tpi): 32 Thread Size: 0.190 inches
Thready Qty Per Inch (tpi): 32 Thread Size: 0.190 inches Material:
Thready Qty Per Inch (tpi): 32 Thread Size: 0.190 inches Material: Iron alloy 660 nut
Thready Qty Per Inch (tpi): 32 Thread Size: 0.190 inches Material: Iron alloy 660 nut Material Specification:
Thready Qty Per Inch (tpi): 32 Thread Size: 0.190 inches Material: Iron alloy 660 nut Material Specification: Ams 5525 assn standard single material response nut
Thready Qty Per Inch (tpi): 32 Thread Size: 0.190 inches Material: Iron alloy 660 nut Material Specification: Ams 5525 assn standard single material response nut Surface Treatment:
Thready Qty Per Inch (tpi): 32 Thread Size: 0.190 inches Material: Iron alloy 660 nut Material Specification: Ams 5525 assn standard single material response nut Surface Treatment: Anodize channel
Thready Qty Per Inch (tpi): 32 Thread Size: 0.190 inches Material: Iron alloy 660 nut Material Specification: Ams 5525 assn standard single material response nut Surface Treatment: Anodize channel Surface Treatment Specification:
Thready Qty Per Inch (tpi):3232Thread Size:0.190 inchesMaterial:Iron alloy 660 nutMaterial Specification:Ams 5525 assn standard single material response nutSurface Treatment:Anodize channelSurface Treatment Specification:Mil-a-8625 military specification single treatment response channel

---



Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-a-8625 spec.