

View Online at <https://aerobasegroup.com/nsn/5310-00-616-6354>

Hole Diameter:

Between 0.576 inches and 0.596 inches

Outside Diameter:

Between 0.960 inches and 0.985 inches

Material Thickness:

Between 0.037 inches and 0.045 inches

End Application:

Helicopter, mh-53e; helicopter, carrier based asw, sh-60f; airborne mobile dir air spt ctl (2id), (02m jul83)(an/uyq-3a); radar set, firefinder (an/tpq-36); aircraft, prowler ea-6b; helicopter, search and rescue, hh-60h; aircraft, c-2a (reprocured); helicopter, uscg search and rescue, hh-60j; helicopter, advance attack, ah-1w; support equipment, b-1 aircraft

Hardness Rating:

Between 40.0 rockwell c and 50.0 rockwell c

Material:

Steel comp 1050 or steel comp 1551 or steel comp 1552 or steel comp 1053 or steel comp 1055 or steel comp 1060 or steel comp 1561

Material Specification:

66 federal standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Style Designator:

Flat external teeth

Specification Or Standard:

1 type and a grade and 1 style and 1 composition

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A022b0