

View Online at <https://aerobasegroup.com/nsn/5310-00-619-5433>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque with nonmetallic insert

Mounting Hole Diameter:

Between 0.098 inches and 0.103 inches

Nut Style:

Plate

Nut Length:

Between 0.954 inches and 0.984 inches

Nut Height:

Between 0.266 inches and 0.296 inches

Plate Thickness:

Between 0.027 inches and 0.037 inches

Plate Width:

Between 0.516 inches and 0.546 inches

Nut Mounting Provision:

Countersunk holes

Mounting Provision Location:

Opposite nut projection side

Mounting Hole Arrangement Style:

2 holes

Distance From Aperture Center To Mounting Hole Center:

Between 0.339 inches and 0.349 inches

Center To Center Distance Between Mounting Holes Along Length:

Between 0.686 inches and 0.690 inches

Temperature Rating:

250.0 degrees fahrenheit

Thread Series:

Unf

Features Provided:

Floating nut

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Mounting Hole Countersink Angle:

100.0 degrees

Material:

Steel comp 1212 nut

Material Specification:

Ams5010 assn standard single material response nut

Surface Treatment:

Cadmium nut

Surface Treatment Specification:

Qq-p-416, type 1, class 3 federal specification single treatment response nut

Specification Or Standard:

250 degrees f type

Departure From Cited Document:

As modified by material

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A021a0

Mil-std (military Standard):

Mil-a-8625 spec.