## NSN 5310-00-619-5434



Plate Self-locking Nut - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5310-00-619-5434 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque with nonmetallic insert **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches **Nut Style:** Plate **Nut Length:** Between 1.266 inches and 1.296 inches **Nut Height:** 0.345 inches **Plate Thickness:** Between 0.027 inches and 0.037 inches Plate Width: Between 0.579 inches and 0.609 inches **Nut Mounting Provision:** Countersunk holes **Mounting Provision Location:** Opposite nut projection side **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.495 inches and 0.505 inches **Center To Center Distance Between Mounting Holes Along Length:** Between 0.998 inches and 1.002 inches **Thread Series:** Unf **Features Provided:** Floating nut Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Mounting Hole Countersink Angle:** 100.0 degrees Material:

Steel comp 1212 nut

**Material Specification:** 

Ams5010 assn standard single material response nut

## NSN 5310-00-619-5434

Plate Self-locking Nut - Page 2 of 2



Surface Treatmer
------------------

Cadmium except insert

**Surface Treatment Specification:** 

Qq-p-416, type 1, class 3 federal specification single treatment response except insert

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A021a0