NSN 5310-00-619-6280

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-619-6280 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque with nonmetallic insert **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches **Nut Style:** Plate **Nut Length:** Between 0.610 inches and 0.640 inches **Nut Height:** Between 0.207 inches and 0.227 inches **Plate Thickness:** Between 0.050 inches and 0.070 inches **Nut Mounting Provision:** Countersunk holes **Mounting Provision Location:** Opposite nut projection side **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.329 inches and 0.359 inches **Tempurature Rating:** 250.0 degrees fahrenheit **Thread Series:** Unc Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches **Mounting Hole Countersink Angle:** 100.0 degrees Material: Plastic polyamide locking insert **Surface Treatment:** Anodize except insert **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response except insert

Shelf Life:

N/a

NSN 5310-00-619-6280

Plate Self-locking Nut - Page 2 of 2



| ι | Jnit | Of | Measure: |
|---|-------|----|-----------|
| • | ,,,,, | • | moudai c. |

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-a-8625 spec.