

View Online at <https://aerobasegroup.com/nsn/5310-00-622-1724>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque with nonmetallic insert

Nut Style:

Hexagon

Nut Height:

0.095 inches

End Application:

Aircraft, (ac-130h, mc-130h, ec-130e, hc-130); tactical air opns module (an/tyq (23); missile, all-weather anti-ship, harpoon (agm-84); radar set, an/pps-5b; missile, air-to-air, sparrow (aim-7); test consoles, mini-sace; support equipment, b-52 aircraft; aircraft, c-2a (reprocured); airborne mobile dir air spt ctl (2id), (02m jul83)(an/uyq-3a)

Width Across Flats:

Between 0.155 inches and 0.158 inches

Temperature Rating:

250.0 degrees fahrenheit

Thread Series:

Unc

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Bearing Surface Type:

Washer faced

Material:

Plastic polyamide locking insert

Material Specification:

Qq-a-365 federal specification single material response nut

Surface Treatment:

Anodize nut

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A021a0

Mil-std (military Standard):

Mil-c-5541 spec.