

View Online at <https://aerobasegroup.com/nsn/5310-00-624-6714>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Drive Point Depth:**

0.180 inches

**Nut Style:**

Round

**Nut Diameter:**

1.730 inches

**Nut Thickness:**

0.350 inches

**Drive Point Quantity:**

4

**Drive Point Diameter:**

Between 0.186 inches and 0.193 inches

**Drilled Hole Diameter:**

Between 0.069 inches and 0.074 inches

**Hole Type And Quantity:**

4 drilled

**Width Across Flats:**

Between 1.552 inches and 1.564 inches

**Thread Series:**

Unef

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.188 inches

**Hole Configuration Style:**

Configuration j

**Special Features:**

2 sides flatted, hole configuration drilled perpendicular to and through drive points

**Material:**

Steel comp 4130 or steel comp 4340

**Material Specification:**

Mil-s-6758 military specification single material response or mil-s-5000, cond c1 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Test Data Document:**

81349-mil-s-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 97499-bps 4075

specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0

**Mil-std (military Standard):**

Mil-s-6758 spec.