

View Online at <https://aerobasegroup.com/nsn/5310-00-624-6714>

Thread Class:

3b

Thread Direction:

Right-hand

Drive Point Depth:

0.180 inches

Nut Style:

Round

Nut Diameter:

1.730 inches

Nut Thickness:

0.350 inches

Drive Point Quantity:

4

Drive Point Diameter:

Between 0.186 inches and 0.193 inches

Drilled Hole Diameter:

Between 0.069 inches and 0.074 inches

Hole Type And Quantity:

4 drilled

Width Across Flats:

Between 1.552 inches and 1.564 inches

Thread Series:

Unef

Thready Qty Per Inch (tpi):

18

Thread Size:

1.188 inches

Hole Configuration Style:

Configuration j

Special Features:

2 sides flatted, hole configuration drilled perpendicular to and through drive points

Material:

Steel comp 4130 or steel comp 4340

Material Specification:

Mil-s-6758 military specification single material response or mil-s-5000, cond c1 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Test Data Document:

81349-mil-s-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 97499-bps 4075

specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-s-6758 spec.