

View Online at <https://aerobasegroup.com/nsn/5310-00-660-3386>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque with nonmetallic insert

Lubrication:

Dry film lubricant or soluble lubricant

Mounting Hole Diameter:

Between 0.098 inches and 0.103 inches

Nut Style:

Plate

Nut Length:

0.984 inches

Nut Height:

0.312 inches

Plate Thickness:

0.075 inches

Plate Width:

0.416 inches

Nut Mounting Provision:

Countersunk holes

Mounting Provision Location:

Opposite nut projection side

Mounting Hole Arrangement Style:

2 holes

Distance From Aperture Center To Mounting Hole Center:

0.344 inches

Center To Center Distance Between Mounting Holes Along Length:

Between 0.686 inches and 0.690 inches

Temperature Rating:

250.0 degrees fahrenheit

Thread Series:

Unjf

Features Provided:

Floating nut

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Countersink Angle:

120.0 degrees nut

Mounting Hole Countersink Angle:

Between 98.0 degrees and 102.0 degrees

Material:

Steel nut

Surface Treatment:

Oxide film shell and cadmium shell

Surface Treatment Specification:

Mil-c-5541 military specification 1st treatment response shell and qq-p-416, type 2, cl 1, 2 or 3 federal specification 2nd treatment response shell

Specification Data:

80205-nas1031 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-c-5541 spec.