Hexagon Self-locking Nut - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-00-680-5669

Build Build Firead Direction: Right-hand Locking Feature: Prevailing torque all metal design Nut Height: 0.188 inches Width Across Flats: Between 0.366 inches and 0.377 inches Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Unf Thread Squ yer Inch (tpl): 32 Bearing Surface Type: Any acceptable Bearing Surface Type: Anodize Specification Data: Bo205-nast J022 professional/industrial association standard Sheif Life: Iva Fig: Ayetao	Thread Class:
Firead Direction: Right-hand Locking Feature: Prevailing torque all metal design Mutheighe: 0.188 inches Width Across Flats: Betwen 0.365 inches and 0.377 inches Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Urf Parlense Rating: Not rated Thread Series: 0.190 inches Betreen O.365 inches stating: Not rated Thread Size: 0.190 inches Betreen Series: Dirace Stating: Aureines Auge: Betrein Surface Type: Ayacceptable Material: Auroinum alloy Surface Treatment: Anolize Specification Data: Bottof Measure: rate Circ Measure: rate Piniltarization: rate Fig:	
Right-hand Locking Feature: Prevailing torque all metal design Nut Heighe: 0.181 Inches Width Across Flats: Between 0.365 inches and 0.377 inches Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Unf Thready Oty Per Inch (tpi): 32 Parferads Rating: Not rated Thready Stats: 0.190 inches Bearing Surface Type: Any acceptable Material: Auminum alloy Surface Treatment: Anodize Paperficiation Data: Apid Measure: Not Tor Measure: Not Surface Treatment: Anodize Paperficiation Data: Not Tor Measure: Na Paperficiation: Na Paperficiation: Na Paperficiation: Na Paperficiation: Na Pa	
Locking Feature: Prevailing torque all metal design Nut Heigh: 0.188 inches Width Across Flats: Between 0.365 inches and 0.377 inches Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Unf Thready Gty Per Inch (tpl): 32 Hardness Rating: Not rated Bearing Surface Type: Any acceptable Material: Auronalous Surface Treatment: Anodize Surface Treatment: Anodize Surface Treatment: No Naterial: Pacelification Data: Boxing Life Heades: Naterial: Na Ditt Of Measure: Na Dittatization: Na Builtatization: Na Builtatization:	
Prevailing torque all metal design Nut Heigh: 0.188 inches Vidth Across Flats: Between 0.365 inches and 0.377 inches Temparature Rating: 250.0 degrees fahrenheit Thread Series: Unf Thread Series: Out 32 Hardness Rating: Not rated Bearing Surface Type: Any acceptable Material: Auoreptable Surface Treatment: Anodze Specification Data: Roodzen-natio22 professional/industrial association standard Mot Measure: Na Fig:	-
Nut Height: 0.188 inches Width Across Flats: Between 0.365 inches and 0.377 inches Tempurature Rating: 25.0.0 degrees fahrenheit Thread Series: Urf Thready Qty Per Inch (tpi): 32 Hardness Rating: Not rated Thread Size: 0.190 inches Bearing Surface Type: Any acceptable Material: Auroinum alloy Surface Treatment: Androlze Specification Data: 80205-nas1022 professional/industrial association standard Shell Life: N/a Final: Naterial: Auroinum alloy Surface Treatment: Anolize Specification Data: Bout Contexting Naterial: Nata Built of Measure: Na Specification Data: Bout Contexting Bout Contexting Bout Contexting Bout Contexting Bout Contexting	
0.188 inchesWidth Across Flats:Between 0.365 inches and 0.377 inchesTempurature Rating:250.0 degrees fahrenheitThread Series:UnfThready Qty Per Inch (tpi):32Hardness Rating:Not ratedThread Size:0.190 inchesBearing Surface Type:Any acceptableMaterial:Aurinum alloySurface Treatment:AnodizeSurface Treatment:AnodizeDie Heife:NoFig:In of Measure:In of Measure: </th <th></th>	
Width Across Flats:Between 0.365 inches and 0.377 inchesFempurature Rating:250.0 degrees fahrenheitThread Series:UnfThready Qty Per Inch (tpl):32Hardness Rating:Not ratedThread Size:0.190 inchesBaring Surface Type:Any acceptableMurium alloySurface Treatment:AnodizeSpecification Data:80205-nas 1022 professional/industrial association standardMateriNaPinel Life:NaFinel Life:NaFinel Life:NaFinel Life:NaSurface The Life:NaSurface The Life:NaSurface The Life:Surface The Life:NaSurface The Life:Surface The Life: <tr< th=""><th></th></tr<>	
Between 0.385 inches and 0.377 inches Forepurature Rating: 250.0 degrees fahrenheit Thread Series: Unf Thready Cyp Per Inch (tpi): 32 Hardness Rating: Not rated Thread Size: 0.190 inches Bearing Surface Type: Any acceptable Material: Audinum alloy Surface Treatment: Anodize Specification Data: 82025-nas1022 professional/industrial association standard Shelf Life: Na Pinel Measure: Init of Measure: Image: No Fig:	
Fempurature Rating: 250.0 degrees fahrenheit Thread Series: Unf Thready Oty Per Inch (tpi): 32 Hardness Rating: Not rated Thread Size: 0.190 inches Bearing Surface Type: Any acceptable Material: Auminum alloy Surface Treatment: Anodize Specification Data: 82056-nas1022 professional/industrial association standard Sheff Life: Ivia of Measure: Ivia of Measure:	
250.0 degrees fahrenheit Thread Series: Unf 7hready Oty Per Inch (tpi): 32 Hardness Rating: Not rated Thread Size: 0.190 inches Bearing Surface Type: Any acceptable Material: Auminum alloy Surface Treatment: Anodize Specification Data: Rot Ti Measure: Na Init of Measure: Init of Measure: No Pinelitarization: No Fig:	
Thread Series: Unf Thready Qty Per Inch (tpi): 32 Hardness Rating: Not rated Thread Size: 0.190 inches Bearing Surface Type: Any acceptable Metrial: Aluminum alloy Surface Treatment: Anodize Specification Data: 80205-nas1022 professional/industrial association standard Surface Treatment: Na Init of Measure: - Pomilitarization: No Fig:	
Unf Fready Qty Per Inch (tpi): 32 Fardness Rating: Not rated Thread Size: 0.190 inches Bearing Surface Type: Any acceptable Material: Auwinum alloy Surface Treatment: Anodize Specification Data: 80205-nas1022 professional/industrial association standard Shelf Life: Na Inf Of Measure: - Pomilitarization: No Fig:	
32 Hardness Rating: Not rated Thread Size: 0.190 inches Bearing Surface Type: Any acceptable Material: Aluminum alloy Surface Treatment: Anodize Specification Data: 80205-nas1022 professional/industrial association standard Shelf Life: N/a Int Of Measure: Fine: No Fig:	
32 Hardness Rating: Not rated Thread Size: 0.190 inches Bearing Surface Type: Any acceptable Material: Aluminum alloy Surface Treatment: Anodize Specification Data: 80205-nas1022 professional/industrial association standard Shelf Life: N/a Int Of Measure: Fine: No Fig:	Thready Qty Per Inch (tpi):
Not rated Thread Size: O.190 inches Bearing Surface Type: Any acceptable Material: Aluminum alloy Surface Treatment: Anodize Specification Data: 80205-nas1022 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Thread Size: 0.190 inches Bearing Surface Type: Any acceptable Material: Aluminum alloy Surface Treatment: Anodize Specification Data: 80205-nas1022 professional/industrial association standard Shelf Life: N/a Int Of Measure: Pomilitarization: No Fig:	Hardness Rating:
0.190 inches Bearing Surface Type: Any acceptable Material: Aluminum alloy Surface Treatment: Anodize Specification Data: 80205-nas1022 professional/industrial association standard Sheff Life: N/a Ditt Of Measure: Demilitarization: No	Not rated
Bearing Surface Type:Any acceptableMaterial:Aluminum alloySurface Treatment:AnodizeSpecification Data:80205-nas1022 professional/industrial association standardShelf Life:N/aUnit Of Measure:-Pomilitarization:NoFig:	Thread Size:
Any acceptableMaterial:Aluminum alloySurface Treatment:AnodizeSpecification Data:80205-nas1022 professional/industrial association standardShelf Life:N/aUnit Of Measure:-Pomilitarization:NoFig:	0.190 inches
Material:Aluminum alloySurface Treatment:AnodizeSpecification Data:80205-nas1022 professional/industrial association standardShelf Life:N/aUnit Of Measure:Pomilitarization:NoFig:	Bearing Surface Type:
Aluminum alloy Surface Treatment: Anodize Specification Data: 80205-nas1022 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Any acceptable
Surface Treatment: Anodize Specification Data: 80205-nas1022 professional/industrial association standard Shelf Life: N/a Nit Of Measure: Demilitarization: No	Material:
Anodize Specification Data: 80205-nas1022 professional/industrial association standard Shelf Life: N/a Init Of Measure: Fomilitarization: No Fig:	Aluminum alloy
Specification Data: 80205-nas1022 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Surface Treatment:
80205-nas1022 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Anodize
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Specification Data:
N/a Unit Of Measure: Demilitarization: No Fiig:	80205-nas1022 professional/industrial association standard
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Filg:	Unit Of Measure:
No Filg:	
Fiig:	Demilitarization:
A021a0	
	A021a0