

View Online at <https://aerobasegroup.com/nsn/5310-00-685-3228>

Hole Diameter:

Between 0.448 inches and 0.464 inches

Outside Diameter:

Between 0.740 inches and 0.789 inches

Material Thickness:

Between 0.032 inches and 0.040 inches

End Application:

W/s: truck, heavy expanded mobility tactical (hemtt); m1a2 abrams tank, 2350-01-328-5964 (eaa cmbt85pk3); missile, advanced medium range air-to-air (amraam)/aim120a; support equipment, b-1 aircraft; aircraft, c-18a, ec-18b; helicopter landing system, lamps mk iii; smoke generator set, m157a2; radar set, an/pps-5b; armored security vehicle, model xm1117; tactical air opns module (an/tyq (23))

Hardness Rating:

Between 40.0 rockwell c and 50.0 rockwell c

Material:

Steel comp 1060 or steel comp 1070 or steel comp 1078 or steel comp 1080

Material Specification:

66 federal standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Style Designator:

Flat internal teeth

Specification Or Standard:

1 type and a grade and 1 style and 1 composition

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A022b0