## NSN 5310-00-688-1998

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-688-1998 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque with nonmetallic insert Lubrication: Dry film lubricant **Mounting Hole Diameter:** Between 0.161 inches and 0.166 inches **Nut Style:** Plate **Nut Length:** 1.602 inches **Nut Height:** 0.630 inches **Plate Thickness:** 0.115 inches Plate Width: 0.859 inches **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style: Distance From Aperture Center To Mounting Hole Center:** 0.625 inches **Center To Center Distance Between Mounting Holes Along Length:** Between 1.248 inches and 1.252 inches **Tempurature Rating:** 250.0 degrees fahrenheit **Thread Series:** Unif **Features Provided:** Floating nut Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.500 inches **Countersink Angle:** 

120.0 degrees nut Material: Steel nut

## NSN 5310-00-688-1998

Plate Self-locking Nut - Page 2 of 2



Surface Treatme
-----------------

Cadmium nut

## **Surface Treatment Specification:**

Qq-p-416 type 2 cl 1 federal specification 1st treatment response nut or qq-p-416 type 2 cl 2 federal specification 1st treatment response nut or qq-p-416 type 2 cl 3 federal specification 1st treatment response nut

nelf	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-a-8625 spec.