

View Online at <https://aerobasegroup.com/nsn/5310-00-688-1998>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque with nonmetallic insert

**Lubrication:**

Dry film lubricant

**Mounting Hole Diameter:**

Between 0.161 inches and 0.166 inches

**Nut Style:**

Plate

**Nut Length:**

1.602 inches

**Nut Height:**

0.630 inches

**Plate Thickness:**

0.115 inches

**Plate Width:**

0.859 inches

**Nut Mounting Provision:**

Straight holes

**Mounting Hole Arrangement Style:**

2 holes

**Distance From Aperture Center To Mounting Hole Center:**

0.625 inches

**Center To Center Distance Between Mounting Holes Along Length:**

Between 1.248 inches and 1.252 inches

**Temperature Rating:**

250.0 degrees fahrenheit

**Thread Series:**

Unjf

**Features Provided:**

Floating nut

**Thready Qty Per Inch (tpi):**

20

**Thread Size:**

0.500 inches

**Countersink Angle:**

120.0 degrees nut

**Material:**

Steel nut

**Surface Treatment:**

Cadmium nut

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 1 federal specification 1st treatment response nut or qq-p-416 type 2 cl 2 federal specification 1st treatment response nut or qq-p-416 type 2 cl 3 federal specification 1st treatment response nut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0

**Mil-std (military Standard):**

Mil-a-8625 spec.