## NSN 5310-00-728-5512



Plate Self-locking Nut - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5310-00-728-5512 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque with nonmetallic insert **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches **Nut Style:** Plate **Nut Length:** 1.296 inches **Nut Height:** Between 0.240 inches and 0.375 inches **Plate Thickness:** 0.075 inches Plate Width: Between 0.484 inches and 0.516 inches **Nut Mounting Provision:** Countersunk holes **Mounting Provision Location:** Opposite nut projection side **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.495 inches and 0.505 inches **Center To Center Distance Between Mounting Holes Along Length:** Between 0.998 inches and 1.002 inches **Tempurature Rating:** 250.0 degrees fahrenheit **Thread Series:** Unif Thready Qty Per Inch (tpi): 28 **Hardness Rating:** 32.0 rockwell c **Thread Size:** 0.250 inches **Mounting Hole Countersink Angle:** 

Material: Steel nut

Between 98.0 degrees and 102.0 degrees

## NSN 5310-00-728-5512

Plate Self-locking Nut - Page 2 of 2



O	·	<b>T</b>	4	
SHILL	ace	Trea	tme	nt.

Cadmium except insert and chromate except insert

**Surface Treatment Specification:** 

Qq-p-416, type 2, class 3 federal specification single treatment response except insert

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A021a0