NSN 5310-00-728-5515



Plate Self-locking Nut - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5310-00-728-5515 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque with nonmetallic insert **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches **Nut Style:** Plate **Nut Length:** 1.031 inches **Nut Height:** Between 0.234 inches and 0.312 inches **Plate Thickness:** 0.075 inches Plate Width: Between 0.375 inches and 0.406 inches **Nut Mounting Provision:** Countersunk holes **Mounting Provision Location:** Opposite nut projection side **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.339 inches and 0.349 inches **Center To Center Distance Between Mounting Holes Along Length:** Between 0.310 inches and 0.314 inches **Tempurature Rating:** 250.0 degrees fahrenheit **Thread Series:** Unif Thready Qty Per Inch (tpi): 32 **Hardness Rating:**

32.0 rockwell c **Thread Size:** 0.190 inches **Mounting Hole Countersink Angle:** Between 98.0 degrees and 102.0 degrees Material: Steel nut

NSN 5310-00-728-5515

Plate Self-locking Nut - Page 2 of 2



_	•		_	-		
ن	ırfa	\sim	I ro	-atn	nor	٠.

Cadmium except insert and chromate except insert

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response except insert

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0