NSN 5310-00-728-5516



Plate Self-locking Nut - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5310-00-728-5516 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque with nonmetallic insert **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches **Nut Style:** Plate **Nut Length:** 1.062 inches **Nut Height:** Between 0.240 inches and 0.375 inches **Plate Thickness:** 0.075 inches Plate Width: Between 0.438 inches and 0.516 inches **Nut Mounting Provision:** Countersunk holes or dimpled holes **Mounting Provision Location:** Opposite nut projection side **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.339 inches and 0.349 inches **Center To Center Distance Between Mounting Holes Along Length:** Between 0.310 inches and 0.314 inches **Tempurature Rating:** 250.0 degrees fahrenheit **Thread Series:** Unif Thready Qty Per Inch (tpi):

28 **Hardness Rating:** 32.0 rockwell c **Thread Size:** 0.250 inches **Countersink Angle:** 88.0 degrees nut and 102.0 degrees nut **Mounting Hole Countersink Angle:** Between 98.0 degrees and 102.0 degrees

NSN 5310-00-728-5516

Plate Self-locking Nut - Page 2 of 2

A021a0



| Material: |
|--|
| Steel nut |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 3 federal specification single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiia: |