

View Online at <https://aerobasegroup.com/nsn/5310-00-732-2830>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design

**Counterbore Diameter:**

0.168 inches nut

**Mounting Hole Diameter:**

Between 0.098 inches and 0.103 inches

**Nut Style:**

Plate

**Nut Length:**

0.935 inches

**Nut Height:**

0.250 inches

**Plate Thickness:**

0.047 inches

**Plate Width:**

Between 0.277 inches and 0.297 inches

**Nut Counterbore Depth:**

0.062 inches nut

**Nut Mounting Provision:**

Countersunk holes

**Mounting Provision Location:**

Opposite nut projection side

**Mounting Hole Arrangement Style:**

2 holes

**Distance From Aperture Center To Mounting Hole Center:**

Between 0.339 inches and 0.349 inches

**Center To Center Distance Between Mounting Holes Along Length:**

Between 0.310 inches and 0.314 inches

**Temperature Rating:**

800.0 degrees fahrenheit

**Thread Series:**

Unjc

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

49.0 rockwell c

**Thread Size:**

0.164 inches

**Mounting Hole Countersink Angle:**

Between 98.0 degrees and 102.0 degrees

**Product Name:**

Nut, self-locking, plate

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5732 assn standard single material response or ams 5737 assn standard single material response or ams 5525 assn standard single material response

**Precious Material And Location:**

All surfaces silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver

**Surface Treatment Specification:**

Ams 2410 assn standard single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A021a0