NSN 5310-00-734-1638

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-734-1638 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design Lubrication: Dry film lubricant **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches **Nut Style:** Plate **Nut Length:** 0.822 inches **Nut Height:** 0.281 inches **Plate Thickness:** 0.055 inches Plate Width: Between 0.380 inches and 0.414 inches **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.276 inches and 0.286 inches **Center To Center Distance Between Mounting Holes Along Length:** Between 0.217 inches and 0.221 inches **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** Unif Thready Qty Per Inch (tpi): 28 **Hardness Rating:** 49.0 rockwell c **Thread Size:** 0.250 inches

Material:

Iron alloy 660

Material Specification:

Ams 5732 assn standard single material response or ams 5737 assn standard single material response or ams 5525 assn standard single material response

NSN 5310-00-734-1638

Plate Self-locking Nut - Page 2 of 2



_				_			
	111	20	Δ.	I rc	1 0t	mc	nt:
31	41	au		115	za L	1116	71 IL.

Passivate

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0