## NSN 5310-00-736-6398

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-736-6398 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design **Counterbore Diameter:** 0.194 inches nut Lubrication: Dry film lubricant **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches **Nut Style:** Plate **Nut Length:** 0.521 inches **Nut Height:** 0.250 inches **Plate Thickness:** 0.047 inches Plate Width: 0.437 inches **Nut Counterbore Depth:** 0.062 inches nut **Nut Mounting Provision:** Countersunk holes **Mounting Provision Location:** Opposite nut projection side **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.245 inches and 0.255 inches **Center To Center Distance Between Mounting Holes Along Width:** Between 0.217 inches and 0.221 inches **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** Unjf Thready Qty Per Inch (tpi):

32

**Thread Size:** 

0.190 inches

## NSN 5310-00-736-6398

Plate Self-locking Nut - Page 2 of 2

No Fiig: A021a0



Mounting Hole Countersink Angle:
Between 98.0 degrees and 102.0 degrees
Material:
Steel
Surface Treatment:
Cadmium
Surface Treatment Specification:
$\ensuremath{Qq\text{-}p\text{-}416},\ \ensuremath{type}\ \ensuremath{1},\ \ensuremath{cl}\ \ensuremath{3}\ \ensuremath{federal}\ \ensuremath{specification}\ \ensuremath{single}\ \ensuremath{treatment}\ \ensuremath{response}\ \ensuremath{a}$
Specification Data:
80205-nas1067 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: