

View Online at https://aerobasegroup.com/nsn/5310-00-740-9369

| Thread Class: | |
|-------------------|---|
| 2b | |
| Thread Direction | n: |
| Right-hand | |
| Locking Feature | e: |
| Prevailing torque | all metal design |
| Nut Style: | |
| Single ball seat, | hexagon |
| Ball Seat Radius | S: |
| Between 0.484 in | nches and 0.516 inches |
| Nut Height: | |
| Between 0.609 ir | nches and 0.641 inches |
| Width Across Fl | lats: |
| Between 0.859 ir | nches and 0.891 inches |
| Thread Series: | |
| Unf | |
| Thready Qty Per | r Inch (tpi): |
| 24 | |
| Thread Size: | |
| 0.375 inches | |
| Material: | |
| Steel comp 1213 | or steel comp 1117 |
| Material Specific | cation: |
| Aisi assn standar | rd all material responses |
| Surface Treatme | ent: |
| Cadmium or zind | c and chromate |
| Surface Treatme | ent Specification: |
| Qq-p-416, type 2 | , class 3 federal specification 1st treatment response or qq-z-325, type 2, class 3 federal specification 2nd treatment |
| response | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure | |
| | |
| Demilitarization | : |
| No | |
| Fiig: | |
| A021a0 | |