

View Online at <https://aerobasegroup.com/nsn/5310-00-757-5909>

**Thread Pitch Diameters:**

+2.1209/+2.1260 inches

**Thread Direction:**

Right-hand

**Drive Point Depth:**

0.125 inches

**Nut Style:**

Round

**Nut Diameter:**

Between 2.953 inches and 2.973 inches

**Nut Thickness:**

Between 0.490 inches and 0.510 inches

**Drive Point Width:**

Between 0.240 inches and 0.260 inches

**Drive Point Quantity:**

4

**Thread Series:**

Uns

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

2.156 inches

**Countersink Angle:**

45.0 degrees second end and 60.0 degrees second end

**Material:**

Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1026 or steel comp 1527 or steel comp 1029 or steel comp 1030 or steel comp 1035

**Material Specification:**

66 federal standard all material responses

**Surface Treatment:**

Cadmium or chromate zinc

**Surface Treatment Specification:**

Qq-p, 416, type 2, class 3 federal specification 1st treatment response or qq-z-325, type 2, class3 federal specification 2nd treatment response

**Specification Or Standard:**

1 type and 1 class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0