NSN 5310-00-762-2917

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-762-2917 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design **Counterbore Diameter:** 0.254 inches nut **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches **Nut Style:** Plate **Nut Length:** 0.993 inches **Nut Height:** 0.281 inches **Plate Thickness:** 0.055 inches Plate Width: Between 0.375 inches and 0.414 inches **Nut Counterbore Depth:** 0.062 inches nut **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.339 inches and 0.349 inches Center To Center Distance Between Mounting Holes Along Length: Between 0.310 inches and 0.314 inches **Tempurature Rating:** 800.0 degrees fahrenheit **Thread Series:** Unjf Thready Qty Per Inch (tpi): **Hardness Rating:** 49.0 rockwell c **Thread Size:** 0.250 inches

Material: Iron alloy 660

NSN 5310-00-762-2917

Plate Self-locking Nut - Page 2 of 2



wateriai Specification	al Specificati	ecificatior	Sp	ial	later	۷
------------------------	----------------	-------------	----	-----	-------	---

Ams 5525 assn standard single material response, or ams 5732 assn standard single material response, or ams 5737 assn standard single

Allis 3023 assit standard single material response of allis 3732 assit standard single material response of allis 3737 assit standard single
material response
Precious Material And Location:
All surfaces silver
Precious Material:
Silver

Surface Treatment Specification:

Ams 2410 assn standard single treatment response

Shelf Life:

Silver

N/a

Unit Of Measure:

Surface Treatment:

Demilitarization:

No

Fiig:

A021a0