NSN 5310-00-762-6156

Plate Self-locking Nut - Page 1 of 2

Thread Class:

3b



View Online at https://aerobasegroup.com/nsn/5310-00-762-6156

| Thread Direction: |
|--|
| Right-hand |
| Locking Feature: |
| Prevailing torque all metal design |
| Lubrication: |
| Soluble lubricant |
| Mounting Hole Diameter: |
| Between 0.098 inches and 0.103 inches |
| Nut Style: |
| Plate |
| Nut Length: |
| 0.661 inches |
| Nut Height: |
| 0.141 inches |
| Plate Thickness: |
| 0.047 inches |
| Plate Width: |
| Between 0.195 inches and 0.265 inches |
| Nut Mounting Provision: |
| Straight holes |
| Mounting Hole Arrangement Style: |
| 2 holes |
| Distance From Aperture Center To Mounting Hole Center: |
| 0.2185 inches |
| Center To Center Distance Between Mounting Holes Along Length: |
| Between 0.435 inches and 0.439 inches |
| Tempurature Rating: |
| 800.0 degrees fahrenheit |
| Thread Series: |
| Unjc |
| Thready Qty Per Inch (tpi): |
| 32 |
| Hardness Rating: |
| 49.0 rockwell c |
| Thread Size: |
| 0.138 inches |
| Material: |
| Iron alloy 660 |
| Material Specification: |

Ams 5735 assn standard single material response or ams 5737 assn standard single material response or ams 5525 assn standard single material response

NSN 5310-00-762-6156

Plate Self-locking Nut - Page 2 of 2



| Precious Material: |
|--|
| Silver |
| Surface Treatment: |
| Silver |
| Surface Treatment Specification: |
| Ams 2410 assn standard single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A021a0