

View Online at <https://aerobasegroup.com/nsn/5310-00-764-0969>

Thread Class:

3b

Thread Pitch Diameters:

+1.1369 to 1.1409 inches

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque with nonmetallic insert

Drive Point Depth:

Between 0.164 inches and 0.204 inches

Nut Style:

Round

Nut Diameter:

Between 1.735 inches and 1.755 inches

Nut Thickness:

Between 0.365 inches and 0.395 inches

Drive Point Width:

0.188 inches

Drive Point Quantity:

4

Temperature Rating:

250.0 degrees fahrenheit

Thread Series:

Uns

Thready Qty Per Inch (tpi):

18

Thread Size:

1.173 inches

Countersink Angle:

100.0 degrees nut

Special Features:

Threads square with bearing surface by 0.001 in.

Material:

Steel comp 4340 nut

Material Specification:

Ams 6415 assn standard single material response nut

Surface Treatment:

Phosphate zinc nut

Surface Treatment Specification:

Mil-prf-16232 type z, class 4 military specification single treatment response nut

Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81205-bacn10gr manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-s-6758 spec.