

View Online at <https://aerobasegroup.com/nsn/5310-00-764-0972>

**Thread Pitch Diameters:**

+1.3399/+1.3439 inches

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque with nonmetallic insert

**Small End Diameter:**

Between 1.640 inches and 1.672 inches

**Drive Point Depth:**

Between 0.083 inches and 0.108 inches

**Nut Style:**

Round

**Nut Diameter:**

Between 1.891 inches and 1.911 inches

**Nut Thickness:**

Between 0.376 inches and 0.396 inches

**Drive Point Width:**

Between 0.172 inches and 0.204 inches

**Undercut Thickness:**

Between 0.054 inches and 0.106 inches

**Drive Point Quantity:**

4

**Thread Series:**

Uns

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.376 inches

**Countersink Angle:**

90.0 degrees nut and 110.0 degrees nut

**Material:**

Steel comp 4130 nut

**Material Specification:**

Mil-s-6758, cond f, surface cond 4 military specification 1st material response nut

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924 military specification single treatment response

**Specification Data:**

81205-bacn10gr manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A021a0

**Mil-std (military Standard):**

Mil-s-6758 spec.