NSN 5310-00-764-1788

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-764-1788 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design Lubrication: Dry film lubricant **Mounting Hole Diameter:** Between 0.130 inches and 0.135 inches **Nut Style:** Plate **Nut Length:** 1.026 inches **Nut Height:** 0.328 inches **Plate Thickness:** 0.065 inches Plate Width: Between 0.475 inches and 0.505 inches **Nut Mounting Provision:** Countersunk holes **Mounting Provision Location:** Opposite nut projection side **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.354 inches and 0.364 inches Center To Center Distance Between Mounting Holes Along Length: Between 0.267 inches and 0.271 inches **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** Unjf Thready Qty Per Inch (tpi): **Hardness Rating:**

49.0 rockwell c

Thread Size:
0.312 inches

Mounting Hole Countersink Angle:
Between 98.0 degrees and 102.0 degrees

NSN 5310-00-764-1788

Plate Self-locking Nut - Page 2 of 2

A021a0



| Material: |
|--|
| Steel |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 3 federal specification single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |