## NSN 5310-00-770-3881

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-770-3881 **Thread Class:** 2b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque with metallic insert **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches **Nut Style:** Plate **Nut Length:** Between 0.580 inches and 0.620 inches **Distance From Base To Center Of Aperture:** Between 0.290 inches and 0.330 inches **Nut Height:** Between 0.520 inches and 0.560 inches **Plate Thickness:** Between 0.040 inches and 0.060 inches Plate Width: Between 1.460 inches and 1.570 inches **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style:** 2 holes **Distance From Mounting Hole Center To Base:** Between 0.230 inches and 0.270 inches **Center To Center Distance Between Mounting Holes Along Width:** Between 1.000 inches and 1.030 inches **Thread Series:** Unf Thready Qty Per Inch (tpi): **Thread Size:** 0.190 inches Material: Stainless steel locking insert **Material Specification:** Qq-a-367 t6 federal specification single material response except insert **Surface Treatment:** 

Anodize except insert

**Surface Treatment Specification:** 

Mil-a-8625 military specification single treatment response except insert

## NSN 5310-00-770-3881

Plate Self-locking Nut - Page 2 of 2



| Sp  | eci | fic | cati | ion | Da | ta: |
|-----|-----|-----|------|-----|----|-----|
| - [ |     |     |      |     |    |     |

81205-bacn10gh manufacturers standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-a-8625 spec.