

View Online at <https://aerobasegroup.com/nsn/5310-00-772-7958>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design

**Mounting Hole Diameter:**

Between 0.098 inches and 0.103 inches

**Nut Style:**

Plate

**Nut Length:**

0.948 inches

**Nut Height:**

0.272 inches

**Plate Thickness:**

0.047 inches

**Plate Width:**

Between 0.360 inches and 0.422 inches

**Nut Mounting Provision:**

Countersunk holes

**Mounting Provision Location:**

Opposite nut projection side

**Mounting Hole Arrangement Style:**

2 holes

**Distance From Aperture Center To Mounting Hole Center:**

Between 0.339 inches and 0.349 inches

**Center To Center Distance Between Mounting Holes Along Length:**

Between 0.686 inches and 0.690 inches

**Temperature Rating:**

800.0 degrees fahrenheit

**Thread Series:**

Unjc

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

49.0 rockwell c

**Thread Size:**

0.164 inches

**Countersink Angle:**

99.0 degrees nut and 101.0 degrees nut

**Mounting Hole Countersink Angle:**

Between 98.0 degrees and 102.0 degrees

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5525 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response

**Precious Material And Location:**

All surfaces silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver

**Surface Treatment Specification:**

Ams 2410 assn standard single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0