

View Online at <https://aerobasegroup.com/nsn/5310-00-773-2314>

Hole Diameter:

Between 0.615 inches and 0.635 inches

Radius:

Between 3.500 inches and 3.502 inches

Outside Diameter:

Between 2.615 inches and 2.635 inches

Recess Diameter:

2.593 inches

Material Thickness:

Between 0.365 inches and 0.385 inches

Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

Surface Finish:

63.0 microinches top

Heat Treatment:

Quenched and tempered

Material:

Steel comp 1040 or steel comp 1042 or steel comp 1045 or steel comp 1046 or steel comp 1548 or steel comp 1050 or steel comp 1137 or steel comp 1139 or steel comp 1140 or steel comp 1141

Material Specification:

Astm a108 assn standard 1st material response or astm a108 assn standard 2nd material response or astm a108 assn standard 3rd material response or astm a108 assn standard 4th material response or astm a108 assn standard 5th material response or astm a108 assn standard 6th material response or qq-s-637 federal specification 7th material response or qq-s-637 federal specification 8th material response or qq-s-637 federal specification 9th material response or qq-s-637 federal specification 10th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 type 2 cl b federal specification single treatment response

Style Designator:

Concave

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A022b0