NSN 5310-00-774-9428



Recessed Washer - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5310-00-774-9428 **Hole Diameter:** Between 0.631 inches and 0.651 inches **Outside Diameter:** Between 1.209 inches and 1.229 inches **Material Thickness:** Between 0.151 inches and 0.161 inches **End Application:** Uh-1n Min. Tensile Strength (psi): 240000 pounds per square inch **Top Recess Diameter:** Between 0.731 inches and 0.741 inches **Bottom Recess Angle:** Between 89.0 degrees and 91.0 degrees **Top Recess Angle:** Between 89.0 degrees and 91.0 degrees **Bottom Recess Diameter:** Between 0.731 inches and 0.741 inches **Surface Finish:** 63.0 microinches all surfaces Material: Steel comp h11 **Material Specification:** Ams 6485 assn standard single material response or ams 6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837, type 2, cl 2 military specification single treatment response **Style Designator:** Recessed both sides Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A022b0

Mil-std (military Standard): Mil-c-8837 spec.