
Plate Self-locking Nut - Page 1 of 2

Thread Class:





3b **Thread Direction: Right-hand** Locking Feature: Prevailing torque all metal design Lubrication: Dry film lubricant **Mounting Hole Diameter:** Between 0.130 inches and 0.135 inches Nut Style: Plate Nut Length: 1.396 inches Nut Height: 0.328 inches **Plate Thickness:** 0.045 inches Plate Width: Between 0.412 inches and 0.641 inches **Nut Mounting Provision:** Countersunk holes **Mounting Provision Location:** Opposite nut projection side **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.495 inches and 0.505 inches Center To Center Distance Between Mounting Holes Along Length: Between 0.310 inches and 0.314 inches **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** Unjf **Features Provided:** Floating nut Thready Qty Per Inch (tpi): 24 Hardness Rating: 49.0 rockwell c **Thread Size:** 0.312 inches

NSN 5310-00-778-9507

Plate Self-locking Nut - Page 2 of 2



Mounting Hole Countersink Angle:

Between 98.0 degrees and 102.0 degrees

Material:

Steel

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A021a0